



BIOMEDICAL REFRIGERATOR + 1° / + 10° C - SOLID DOOR

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
BMR628	628 L	603	694	1500	740	830	2037
					SHIPPING WEIGHT (mm)		
					800	900	2250

CAPACITY	628 L
TEMPERATURE RANGE	+ 1° C / + 10° C
AMBIENT TEMPERATURE	MAX.+ 40° C
NO. OF COMPRESSOR	1
POWER	230V / 50 HZ
ALARMS	VISUAL / ACOUSTIC ALARM • OPEN DOOR ALARM • ALARM DISPLAY AS TEXT - NOT CODES • POWER FAILURE ALARM • ADJUSTABLE HIGH / LOW TEMPERATURE ALARM • APPROX. 48 HRS. OF BATTERY BACKUP FOR ALARMS AND TEMPERATURE DISPLAY IN THE EVENT OF POWER CUT • TRACK OF ALARMS TO BE NOTED AUTOMATICALLY • PROBE FAILURE ALARM • CONTACT REMOTE ALARM
BACK UP	72 HOURS BATTERY BACKUP FOR LOGGING ALARMS & TEMPERATURE DISPLAY IN CASE OF POWER FAILURE
ISOLATION	70 MM
WEIGHT/SHIPPING WEIGHT	125 KG / 175 KG
SHELVES	3
MAX. SHELF LOAD	30 KG
DISPLAY	TOUCH SCREEN • INTERGRATED DATALOGGER • RS485 INTERFACE • USB UP/ DOWN LOAD • MEMORY FOR OVER 15 YEARS OF DATA • DATE & TIME • DIFFERENT LANGUAGES • PASSWORD PROTECTED • TEMPERATURE GRAPH
CASTORS LOCKABLE	4 CASTORS - 2 LOCKABLE
DEFROST	AUTOMATIC
LIGHTING	YES
KEY LOCK	YES
NO. OF DOORS	1 SOLID DOOR
REFRIGERANT	R290
CHAMBER MATERIAL	STAINLESS STEEL
EXTERIOR MATERIAL	POWDER COATED GALVANIZED STEEL
DOCUMENTATION	IQ • OQ • TEMPERATURE MAPPING • VALIDATION GUIDANCE

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

B SCIENCE

Bavnevej 10 • 6580 Vamdrup • Denmark
 info@bscienceglobal.com • www.bscienceglobal.com
 +45 287 287 62

