



## LAB REFRIGERATOR +1° / +10° C - SOLID DOOR

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
LABREF628	628 L	603	694	1500	740	830	2037
					SHIPPING DIMENSION (mm)		
					1000	900	2250

<b>CAPACITY</b>	628 L
<b>TEMPERATURE RANGE</b>	+1° C / +10° C
<b>AMBIENT TEMPERATURE</b>	MAX. + 40° C
<b>NO. OF COMPRESSOR</b>	1
<b>POWER</b>	230V / 50 HZ
<b>ALARMS</b>	VISUAL / ACOUSTIC ALARM ▪ OPEN DOOR ALARM ▪ ADJUSTABLE HIGH / LOW TEMPERATURE ALARM ▪ VOLTAGE FREE CONTENT FOR REMOTE ALARM
<b>ISOLATION</b>	70 MM
<b>WEIGHT</b>	145 KG / 235 KG
<b>SHELVES</b>	3
<b>MAX. SHELF LOAD</b>	30 KG
<b>CONTROLLOR</b>	ELECTRONIC MICROPROCESSOR
<b>CASTORS LOCKABLE</b>	4 CASTORS - 2 LOCKABLE
<b>DEFROST</b>	AUTOMATIC
<b>COOLING</b>	AIR FORCED COOLING
<b>DOOR KEY LOCK</b>	YES
<b>DOOR</b>	MAGNETIC DOOR GASKET ▪ SELF-CLOSING DOOR ▪ SOLID DOOR
<b>NO. OF DOORS</b>	1
<b>REFRIGERANT</b>	R290
<b>CHAMBER MATERIAL</b>	STAINLESS STEEL
<b>EXTERIOR MATERIAL</b>	POWDER COATED GALVANIZED STEEL

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.