

ULTRA LOW TEMPERATURE FREEZER -86° C

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)			SHIPPING DIMENSION (mm)		
		W	D	H	W	D	H	W	D	H
B-ULT550	527 L	610	640	1350	890	920	1997	1160	1110	2250



CAPACITY GROSS/NET	527 L / 502 L
TEMPERATURE RANGE	-86° C / -40° C
AMBIENT TEMPERATURE	MAX.+ 25° C
POWER	230 V / 50 HZ / 5,2 Amp
ENERGY CONSUMPTION	13,4 Kw / 24 Hrs.
WEIGHT / SHIPPING WEIGHT	267 Kg / 400 Kg
MAX. SHELF LOAD	40 Kg Pr. Shelf
COOLING TECHNOLOGY	Cascade Cooling System
INTERFACE	Potential Free Remote Contact & Voltage Free Content For Remote Alarm

ENVIRONMENTAL EFFECT



GWP	3 (R290) / 4 (R1150)
ODP	0 (R290) / 0 (R1150)

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

TECHNICAL DATASHEET

CONSTRUCTION

✓ Chamber Material Stainless Steel	✓ Magnetic Silicone Gasket	✓ Key Lock
✓ 4 pc pre made port hole	✓ Castors	✓ 4 Inner Door
✓ Heated Door Frame	✓ Vacuum release valve	✓ 3 Shelf
✓ Exterior Material Powder Coated Galvanized Steel	✓ Isolation Ecological Polyurethane Foam with V.I.P. Panels 120mm Thickness	

ALARMS

✓ Visual/Acoustic Alarm	✓ Open Door Alarm	✓ Voltage Free Content For Remote Alarm
✓ Power Failure Alarm	✓ Probe Failure Alarm	✓ Compressor Alarm
✓ Adjustable High / Low Temperature Alarm	✓ All Events Automatically Registered	✓ Approx. 72 HRS. of Battery Backup for Alarms and Logging

DISPLAY

✓ Touch Screen	✓ Integrated Data Logger	✓ USB - Up & Download
✓ Memory For Over 15 Years Of Data	✓ Date & Time	✓ Password Protected
✓ Temperature Graph	✓ Integrated Test Mode	✓ Ambient Temperature

OPTIONAL RACKS & BOXES

RACKS	16 pcs	50MM BOXES	352
-------	--------	------------	-----

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.