

TECHNICAL DATASHEET

BIOMEDICAL REFRIGERATOR + 1° / + 10° C - GLASS DOOR

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
BMR628G	628 L	603	694	1500	740	830	2037
					SHIPPING WEIGHT (mm)		
					1000	900	2250



CAPACITY	628 L
TEMPERATURE RANGE	+ 1° C / + 10° C
AMBIENT TEMPERATURE	MAX.+ 32° C
NO. OF COMPRESSOR	1
POWER	230V / 50 HZ
ALARMS	VISUAL / ACOUSTIC ALARM • OPEN DOOR ALARM • POWER FAILURE ALARM • ADJUSTABLE HIGH / LOW TEMPERATURE ALARM • APPROX. 72 HRS. OF BATTERY BACKUP FOR ALARMS AND TEMPERATURE DISPLAY IN THE EVENT OF POWER CUT • ALL EVENTS AUTOMATICALLY REGISTERED • PROBE FAILURE ALARM • VOLTAGE FREE CONTENT FOR REMOTE ALARM
BACK UP	72 HOURS BATTERY BACKUP FOR LOGGING ALARMS & TEMPERATURE DISPLAY IN CASE OF POWER FAILURE
ISOLATION	70 MM
WEIGHT/SHIPPING WEIGHT	125 KG / 210 KG
SHELVES	3
MAX. SHELF LOAD	30 KG
DISPLAY	TOUCH SCREEN • INTEGRATED DATALOGGER • USB UP/ DOWN LOAD MEMORY FOR OVER 15 YEARS OF DATA • DATE & TIME • TEMPERATURE GRAPH AMBIENT TEMPERATURE • DIFFERENT LANGUAGES • PASSWORD PROTECTED
CASTORS LOCKABLE	4 CASTORS - 2 LOCKABLE
DEFROST	AUTOMATIC
LIGHTING	YES
KEY LOCK	YES
NO. OF DOORS	1 GLASS DOOR
REFRIGERANT	R290
CHAMBER MATERIAL	STAINLESS STEEL
EXTERIOR MATERIAL	POWDER COATED GALVANIZED STEEL
PORTHOLES	YES

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.



Bavnevej 20 • 6580 Vamdrup • Denmark
 info@bscienceglobal.com • www.bscienceglobal.com
 +45 287 287 62

