

LBR400, LAB BASIC REFRIGERATOR +1°/+10° C

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)			SHIPPING DIMENSION (mm)		
		W	D	H	W	D	H	W	D	H
LBR400	378 L	500	510	1500	600	700	1900	700	800	2000

CAPACITY	378 L
TEMPERATURE RANGE	+1° / +10° C
AMBIENT TEMPERATURE	MAX 32°C
POWER	230 V - 50 HZ, 1,5 AMP
ENERGY CONSUMPTION	2,8 Kwh/24 Hrs
WEIGHT / SHIPPING WEIGHT	80 kg / 102 kg
MAX. SHELF LOAD	20 kg Per Shelf
COOLING TECHNOLOGY	Air Forced Cooling
INTERFACE	Voltage Free contact for remote alarm



ENVIRONMENTAL EFFEC

GWP 3 (R290)

ODP 0 (R290)



We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

CONSTRUCTION

✓ Interior powder coated aluminium	✓ Isolation 50 mm	✓ Key Lock
✓ 1 pcs of port hole (20mm diameter)	✓ 4 castors	✓ 6 pcs shelves
✓ Light	✓ Exterior powder coated steel	✓ Auto Defrost
✓ Refrigerant R290	✓ Cyclopentane foam	

ALARMS

✓ Visual/Acoustic alarms	✓ Open Door Alarm	✓ Voltage Free Contact For Remote Alarm
✓ Power Failure Alarm	✓ Probe Failure Alarm	✓ Low Battery Alarm
✓ Adjustable High/Low Temperature alarms	✓ Battery back up for logging and alarms	

DISPLAY

✓ Digital Controller	✓ Datalogger	✓ USB for download
----------------------	--------------	--------------------

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.