

BASIC LAB REFRIGERATOR +1/+10° C

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)			SHIPPING DIMENSION (mm)		
		W	D	H	W	D	H	W	D	H
LBR700	618 L	540	740	1460	710	880	1998	800	1000	2250



CAPACITY	618 L
TEMPERATURE RANGE	+1° C / +10° C
AMBIENT TEMPERATURE	MAX.+ 32° C
POWER	230 V / 50 HZ /
ENERGY CONSUMPTION	2,5 Kw / 24 Hrs.
WEIGHT / SHIPPING WEIGHT	150 Kg / 235 Kg
MAX. SHELF LOAD	30 Kg Per. Shelf
COOLING TECHNOLOGY	Air Forced Cooling System
INTERFACE	Potential Free Remote Contact
DOCUMENTATION	IQ • OQ

ENVIRONMENTAL EFFECTS

GWP 3 (R290)

ODP 0 (R290)



We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

CONSTRUCTION

✓ Internal Material Stainless Steel	✓ Replaceable Door Gasket	✓ Key Lock
✓ Self closing doors	✓ Castors	✓ Internal lighth
✓ Exterior Material Powder coated Steel	✓ Isolastion 70mm	✓ 4 Shelf
✓ Auto Defrost		

ALARMS

✓ Visual/Acoustic Alarm	✓ Open Door Alarm	✓ Contact Remote Alarm
✓ Power Failure Alarm	✓ Probe Failure Alarm	
✓ Adjustable High / Low Temperature Alarm	✓ Track of Alarms & Events to be Noted Automatically	✓ Approx 24 HRS. of Battery Backup for Alarms and Logging

DISPLAY

✓ LCD Display	✓ Integrated Datalogger	✓ USB – Download
✓ Memory For Over 15 Years Of Data		

DOCUMENTATION

✓ IQ	✓ OQ
------	------

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.